




PH

PHARMA

X-3 PRESSURE SENSITIVE LABEL HEAD



High-speed, precise web handling

Designed to increase performance and enhance flexibility, WLS' X-3 label head is a fully servomotor-driven system incorporating significant size reduction and design simplification over previous models. A 3-axis mounting assembly with digital settings allows for precise peel plate adjustment and product changeover in minimal time. Pneumatic core chucks are used on the unwind and rewind reels. The renowned WLS "closed loop" push-pull system has been redesigned to allow for easy tool-less disassembly and ease of cleaning.

The X-3's non-proprietary electronics have been conveniently located underneath the label head to reduce wiring between the label head and the main electrical panel, and to allow easy reconfiguration and addition of label heads onto a labeler.

FEATURES AND BENEFITS

- Vertical, horizontal in/out and rotational adjustments with digital setting
- Pneumatic unwind and rewind core chucks
- Push-pull design:
 - "Closed loop" servomotor controlled
 - Isolated web tension (unaffected by unwind or rewind functions)
 - Simple label web threading
 - Tool-less disassembly for easy cleaning
- Synchronized servomotor-driven unwind, push-pull and rewind
- Intermittent or continuous-motion label modes
- Soft start/stop via electronic camming
- Low roll, end of web and broken web detection



X-3 PRESSURE SENSITIVE LABEL HEAD


TYPICAL PRODUCT SPECIFICATIONS

Diameter Roll Size	18" (457 mm) unwind
Core Roll Size	3" (76 mm)
Label Width	0.75" (19 mm) to 4" to 6" (101 mm or 152 mm)
Label Length	Unlimited


Dispensing Speed	<i>Intermittent Mode:</i> Up to 2400 in/min (61 m/min) <i>Continuous Mode:</i> Up to 3750 in/min (95 m/min)
Dispensing Accuracy	+/- 0.0625" (+/- 1.6 mm)

CONFIGURATION

Top view



INTERCEPTOR ON X-3 LABEL HEAD



"CLOSED LOOP" PUSH-PULL ASSEMBLY

OPTIONS

The X-3 can be configured with a variety of options such as label coding and inspection including serialized codes, dual label unwinds, and the Interceptor which automatically removes a rejected label prior to container application.

- Dual unwind
- Integration of most major code printing (including label serialization) and vision inspection brands
- Interceptor for defective label removal prior to application
- Remote Ethernet access (for long distance diagnostics)
- FAT/DDS/IQOQ documentation
- UL, seismic and CE certification

WLS Sales and Service assures responsive and comprehensive technical assistance in solving your labeling application problems, servicing your WLS equipment, and providing a full line of compatible systems supplies.

©2021 ProMach Inc. ProMach reserves the right to change or discontinue specifications and designs shown in this brochure without notice or recourse
PM-WLS-SP107_X3_0121

PHONE
1-866-200-3143

EMAIL
WLS@ProMachBuilt.com

WEB
WeilerLS.com

1256 North Church Street
Moorestown, NJ 08057, USA